

DECLARATION OF PERFORMANCE

DOP: NR. BRD034

(model in accordance with delegated regulation Nr. 574/2014 of the European Commision)

Premiumfol EPDM Dakbedekking 1,20 mm	
EPDM roofsheets for the application of	
waterproofing (flat) roofs for buildings.	
Berdal rubber & plastics BV	
Bedrijvenpark Twente 193	
7602 KG Almelo	
Not applicable	
AVCP 2+	
EN 13956:2012	
Institute with notificationnumber: 0620 (KIWA	
certificate of conformity of the factory production	
control 0063-CPR-109640-1)	

DECLARED PERFORMANCE(S):

Essential characteristics	Performance	Test standard
External fire performance	Froof (to be determined in total roofsystem)	EN 13501-5
Reaction to fire	Class E	EN 13501-1
Watertightness	Pass	EN 1928
Tensile strength (I, w) [N/mm ²]	≥ 8	EN 12311-2B
Elongation (I/w) [%]	≥ 400	EN 12311-2B
Tear resistance (l/w) [N]	≥ 25	EN 12310-2
Joint shear resistance [N/50 mm]	≥ 200	EN 12317-2
Joint peel resistance [N/50 mm]	≥ 50	EN 12316-2
Resistance to static load [kg]	≥ 25	EN 12730
Impact resistance [mm]	≥ 300	EN 12691
Resistance to root penetration	Pass	EN 13948
Foldability at low temperature [°C]	≤ -45	EN 495-5
UV exposure (1.000 h)	Pass	EN 1297
Dangerous substances	Meets requirements	

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance (DoP) is issued in accordance with (EU) Nr. 305/2011, under the sole responsibility of manufacturer identified above

Signed for and on behalf of the manufacturer

B.M.D. van Kamperdijk, General Manager Almelo, The Netherlands, 1 September 2023



MEMBER OF THE BERDAL FAMILY



www.berdal.com/downloads