

DECLARATION OF PERFORMANCE

DOP: NR. BRD041

(model in accordance with delegated regulation Nr. 574/2014 of the European Commission)

Unique identification code of product-type:	Pandser® EPDM ZK-Acryl, BRD041
Intended use/ uses:	Elastic EPDM strips for the application of water vapour control layer for buildings, type A
Manufacturer:	Berdal rubber & plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands
Authorised representative:	Not applicable
The system or systems for assessing and verifying performance resistance (AVCP):	AVCP 3
Harmonised standard:	EN 13984: 2013
Notified authority:	Institute with notification number 0620

DECLARED PERFORMANCE(S):

Essential characteristics	Performance	Test standard
Reaction to fire	Class E	EN 13501-1
Watertightness	Pass	EN 1928
Water vapour resistance coefficient	40.000	EN 1931
Durability (artificial ageing)	Pass	EN 1296 / EN 1931
Tensile strength (l/b)	≥ 5 [N/mm ²]	EN 12311-2
Elongation (l/b)	≥ 300 [%]	EN 12311-2
Tear resistance (l/b)	≥ 60 [N]	EN 12310-1
Joint shear resistance	≥ 45 [N/50 mm]	EN 12317-2
Impact resistance	≥ 250 [mm]	EN 12691
Durability (alkali)	Pass	EN 1847 / EN 12311-2
Dangerous substances	Meets requirements	

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance (DoP) is issued in accordance with (EU) nr. 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer by:



B.M.D. van Kamperdijk, General Manager
Almelo, The Netherlands, 22 March 2021