

## DECLARATION OF PERFORMANCE

### DOP: NR. BRD046

(model in accordance with delegated regulation Nr. 574/2014 of the European Commission)

<b>Unique identification code of product-type:</b>	<b>Pandser EPDM ZK-Acryl</b>
<b>Intended use/ uses:</b>	Elastic EPDM strips for the application of water vapour control layers for buildings, type A
<b>Manufacturer:</b>	Berdal rubber & plastics BV Bedrijvenpark Twente 193 7602 KG Almelo
<b>Authorised representative:</b>	Not applicable
<b>The system or systems for assessing and verifying performance resistance (AVCP):</b>	AVCP 3
<b>Harmonised standard:</b>	EN 13984:2013
<b>Notified authority:</b>	

### DECLARED PERFORMANCE(S):

Essential characteristics	Performance	Test standard
Reaction to fire	Class E	EN 13501-1
Watertightness	Pass	EN 1928
Water vapour resistance coefficient ( $\mu$ )	70.000	EN 1931
Water vapour diffusion after ageing	Pass	EN 1296 / EN 1931
Impact resistance (mm)	NPD (No performance declared)	EN 12691
Joint shear resistance [N/50 mm]	$\geq 45$	EN 12317-2
Tensile strength (l, w) [N/mm <sup>2</sup> ]	$\geq 7$	EN 12311-2B
Elongation (l, w) [%]	$\geq 400$	EN 12311-2B
Tear resistance (l, w) [N]	$\geq 60$	EN 12310-1
Alkali-resistance	Pass	EN 1847 / EN 12311-2B
Dangerous substances	Pass	

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance (DoP) is issued in accordance with (EU) nr. 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer by:



B.M.D. van Kamperdijk, General Manager  
In Almelo on 19 July 2024